

1. A system in a distributed computing environment having a plurality of nodes located across geographically dispersed boundaries, comprising:
 - a server configured with an internationalization application programming interface configured to extract an internationalization context provided by a client device; and

2. The system of claim 1, wherein the resource manager is a database management system.

3. The system of claim 1, wherein the resource manager comprises an application which is configured to use the internationalization context to perform calculations and return a result formatted according to a specification of the internationalization context.

4. The system of claim 1, wherein the internationalization context contains a country identification.

5. The system of claim 1, wherein the internationalization context contains a language identification.

6. The system of claim 1, wherein the internationalization context contains a time zone identifier.

18

8. The system of claim 1, wherein the internationalization context comprises locale information and a time zone identifier.
9. The system of claim 1, wherein the locale information comprises at least one of a country identifier, a language identifier and a currency identifier.
10. A method operative in a distributed computing environment having clients and a plurality of servers located across geographically dispersed boundaries, comprising:
- receiving a first request from a client at a server;
 - receiving a second request from the client at the server, wherein the second request comprises an internationalization context for processing the first request;
 - extracting the internationalization context from the second request; and
 - processing the first request at the server using the internationalization context.
11. The method of claim 10, wherein processing the first request comprises providing the first request and internationalization context to an application to perform calculations using the internationalization context and return a result formatted according to the internationalization context.
12. The method of claim 10, further comprising sending the internationalization context from the server to at least one of the plurality of servers in the distributed computing environment.
13. The method of claim 10, wherein the internationalization context contains a country identifier.
14. The method of claim 10, wherein the internationalization context contains a language identifier.

15. The method of claim 10, wherein the internationalization context contains a time zone identifier.

16. The method of claim 10, wherein the internationalization context contains at least a locale specification and a time zone identifier.

17. The method of claim 16, wherein the locale specification comprises at least one of a country identifier, a language identifier and a currency identifier.

18. The method of claim 10, further comprising processing the first request according to a country identifier of the server if the internationalization context does not contain a country identifier.

19. The method of claim 10, further comprising processing the first request according to a universal time zone identifier if the internationalization context does not contain a time zone identifier of the client.

20. The method of claim 10, further comprising processing the first request according to a time zone identifier of the server if the internationalization context does not contain a time zone identifier.

21. A method operative in a distributed computing environment comprising a client computer and a plurality of server computers, comprising:

receiving, at one of the plurality of server computers, an internationalization context from the client computer, wherein the internationalization context contains at least a locale specification and a time zone identifier; and

processing a request from the client computer according to the internationalization context provided by the client computer.

22. The method of claim 21, wherein the internationalization context contains a country identifier.

23. The method of claim 21, wherein the client and the plurality of servers are located across geographically dispersed boundaries.

24. The method of claim 21, wherein the internationalization context contains a language identifier.

25. The method of claim 21, wherein the internationalization context contains a time zone identifier.

26. The method of claim 21, wherein the locale specification comprises at least one of a country identifier, a language identifier and a currency identifier.

27. A signal bearing medium, comprising a program which, when executed, performs a method, comprising:

- parsing a message from a client computer, wherein the message contains internationalization context;
- extracting the internationalization context from the request; and
- providing the internationalization context to an application in order to configure the application to process a request from the client computer according to the internationalization context provided by the client computer.

28. The signal bearing medium of claim 27, wherein the internationalization context contains a country identifier.

29. The signal bearing medium of claim 27, wherein the internationalization context contains a language identifier.

36. The signal bearing medium of claim 33, wherein the internationalization context contains a country identifier.
37. The signal bearing medium of claim 33, wherein the internationalization context contains a language identifier.
38. The signal bearing medium of claim 33, wherein the internationalization context contains a time zone identifier.
39. The signal bearing medium of claim 33, wherein the internationalization context contains at least a locale specification and a time zone identifier.
40. The signal bearing medium of claim 39, wherein the locale specification comprises at least one of a country identifier, a language identifier and a currency identifier.
41. The signal bearing medium of claim 33, further comprising processing the first request according to a country identifier of the server if the internationalization context does not contain a country identifier.
42. The signal bearing medium of claim 33, further comprising processing the first request according to a time zone identifier provided by the server if the time zone identifier of the internationalization context is set to null.
43. A computer data signal embodied in a transmission medium, comprising an internationalization context containing at least a locale specification and a time zone identifier, wherein the internationalization context configures a processor of a computer to process requests according to the internationalization context.

44. The computer data signal of claim 43, wherein the locale specification comprises at least one of a country identifier, a language identifier and a currency identifier.
45. A method for transparently propagating internationalization context information, comprising:
receiving, at a first computer, a first request from a second computer, the first request including an internationalization context;
extracting the internationalization context from the first request; and
associating the internationalization context with a thread executing at the first computer.
46. The method of claim 45, wherein the internationalization context contains at least a locale specification and a time zone identifier.
47. The method of claim 45, further comprising sending a first main body of the first request to the thread.
48. The method of claim 47, further comprising:
attaching the internationalization context to a second main body to form a second request; and
transmitting the second request to a third computer.
49. The method of claim 48, wherein the second main body is associated with an interface, and wherein the internationalization component is not added to the interface.
50. The method of claim 45, wherein the thread comprises a legacy application thread.
51. The method of claim 45, wherein the internationalization component comprises culture sensitive information.

52. A method for transparently propagating internationalization context information to an application associated with an application interface, the method comprising:

generating a main body of a request; and

attaching an internationalization context to the main body, wherein the internationalization context is not added to the application interface.

53. The method of claim 52, wherein the internationalization context contains at least a locale specification and a time zone identifier.